



i1020 PTZ VIDEO CAMERA

Enterprise-class USB 3.0 full HD PTZ Video Conferencing Camera has positioning for middle and large meeting room video communication.

Features

- Adopted industrial grade ISP, 1/2.8" 5MP sensor, output full HD 1080p with 60 frames per second video streaming, to offer you completely high definition, noiseless and crisp, realistic color image with full details.
- 12x optical zoom lens, with 72.5-degree wide angle FOV, along with smooth pan/tilt rotation and fast, accurate focus to capture any view in conferencing space.
- USB3.0 Output, Plug-and-Play, compatible with your preferred video conferencing software and platform including eNcounter®.
- FECC (far-end camera control supported).
- Standard Sony VISCA and UVC1.5 protocol, PTZ control and firmware upgrade via RS232 and USB port.
- 128 presets supported.
- Support multiple mount way: available to install on desk, monitor, tripod or up-side down in-ceiling.



+1 (480) 922-0044
globalmed.com

15023 N 73rd Street
Scottsdale, AZ 85260
United States



i1020 PTZ VIDEO CAMERA



Package Contents	Camera, Remote Controller, RS232 cable, USB 3.0 cable, Power Supply
Sensor	1/2.8 inch high quality, SONY CMOS sensor, 2.1 MP
Lens	12x optical zoom, 12x digital zoom
View Angle	6.3° (wide) ~72.5° (tele)
Video System	1920x1080p30/25, 1280x720x60/50/30/25
Focal Length	f=3.92(wide)~47.32mm(tele)
S/N Rate	>50dB
Minimum Lux	0.1 lux
Focus	Auto/ Manual
Iris	Auto/ Manual
White Balance	Auto/ Manual
Electronic Shutter	Auto/ Manual
Black Light Compensation	ON/OFF
Anti-Flicker	50Hz/60Hz/OFF
Pan Rotation Angle	-170° ~ +170°
Tilt Rotation Angle	-30° ~ +90°
Pan Rotation Speed	0° ~ 190°/s
Pan Rotation Speed	0° ~ 80°/s
Preset	128 via RS232 control; 10 via remote controller
Video	USB 3.0 (YUY2 format)
Control	RS232 (Sony Visca),, USB 3.0 (UVC1.5 protocol)
Power	DC12V
Camera Dimension	220mmx173mmx117mm
Package Dimension	32x30x31cm